



# BIPRO

TP7G54M  
TP7G54M(H) **108-cell**

390 - 410W

10BB


PERC



- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015
- ISO 14001: 2015
- ISO 45001: 2018



12 25



10BB

2%

0.55%



2%



PID

PID  
85 /85% RH 192



IP68

	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
(Pmax/W)	390	291	395	294	400	298	405	302	410	306
(Vmpp/V)	30.65	28.60	30.85	28.80	31.05	29.00	31.24	29.20	31.43	29.30
(Impp/A)	12.73	10.18	12.81	10.23	12.89	10.30	12.97	10.36	13.05	10.42
(Voc/V)	36.50	34.40	36.75	34.60	37.00	34.80	37.25	35.10	37.50	35.30
(Isc/A)	13.61	10.97	13.69	11.04	13.78	11.11	13.86	11.17	13.94	11.24
(%)	20.00		20.20		20.50		20.70		21.00	

STC : 1000W/m<sup>2</sup>, AM1.5, 25 O-+5W ± 3%  
 NMOT( ) 800W/m<sup>2</sup> AM1.5 20 1m/s

