



TP6L60M  
TP6L60M(H) **120-cell**

**360 - 380W**

9BB Half-cut Mono Perc



### SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems



### PERFORMANCE WARRANTY

**12** Years  
Quality Assurance

**25** Years  
Power Output Guarantee

Linear Performance Warranty

### KEY FEATURES



#### 9BB Half-cut Cell Technology

New circuit design, lower internal current, lower Rs loss  
Ga doped wafer, attenuation <2% (1st year) / 0.55% (Linear)



#### Excellent Anti-PID Performance

2 times of industry standard Anti-PID test



#### Wider Application

No water-permeability and high wear-resistance,  
can be widely used in high-humid, windy and dusty area



#### IP68 Junction Box

High waterproof level

**ELECTRICAL CHARACTERISTICS**

|  |       |       |       |       |       |  |  |
|--|-------|-------|-------|-------|-------|--|--|
|  |       |       |       |       |       |  |  |
|  |       |       |       |       |       |  |  |
|  |       |       |       |       |       |  |  |
|  |       |       |       |       |       |  |  |
|  |       |       |       |       |       |  |  |
|  |       |       |       |       |       |  |  |
|  | 19.70 | 20.00 | 20.30 | 20.60 | 20.90 |  |  |

: C  
C

**MECHANICAL CHARACTERISTICS**

|  |   |
|--|---|
|  | Monocrystalline Silicon (9Busbar)   |
|  | 120pcs in series (6*20)   |
|  | 1755*1038*30mm<br>(69.09*40.87*1.18 inches)                               |
|  | 19.5kg (42.99lbs)   |
|  |   |
|  | Anodized Aluminium Alloy  |
|  | IP68, 3 Bypass Diodes   |
|  | 4mm <sup>2</sup> (IEC), 12AWG(UL)<br>300mm in Length or Customized Length |
|  | T01/LJQ-3-CSY/MC4/MC4-EV02  |

**I-V CURVE**

**TECHNICAL DRAWINGS**

**TEMPERATURE CHARACTERISTICS**

|  |  |
|--|--|
|  |  |
|  |  |
|  |  |
|  |  |

**PACKING CONF**

|  |  |
|--|--|
|  |  |
|  |  |

