



	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
(Pmax/W)	350	261	355	264	360	267	365	270
(Vmpp/V)	33.7	31.1	34.0	31.4	34.3	31.6	34.6	31.9
(Impp/A)	10.40	8.37	10.45	8.43	10.50	8.46	10.56	8.49
(Voc/V)	40.3	37.5	40.5	37.7	40.7	37.9	40.9	38.1
(Isc/A)	11.04	8.91	11.10	8.96	11.15	9.00	11.20	8.96
(%)	19.20		19.50		19.70		19.90	

STC : 1000W/m², AM1.5, 25 0-5W
 NMOT() 800W/m² AM1.5 20 1m/s

	9BB
	120 (6*20)
	1755*1038*30mm (69.09*40.87*1.18)
	19.5kg (42.99lbs)
	3.2mm
	IP68, 3
	4mm ² (IEC), 12AWG(UL) 300mm
	T01/LJQ-3-CSY/MC4/MC4-EVO2

	1000V/1500V/DC
	-40°C~+85°C
	20A
	Class
	5400Pa
	2400Pa

Pmax	-0.36%/°C
Voc	-0.26%/°C
Isc	+0.043%/°C
NMOT	43± 2°C

	36	36(USA)
(40'HC)	988	936

I-V

